Printed on paper from sustainable forests

Distributed by:



C/ Santiago Russinyol, 14 nave C 7-9, Pol. Ind. Can Humet de Dalt 08123 Polinyà, Barcelona, Spain. Tel. +34 93 309 77 83 · info@barnacork.com www.barnacork.com · www.corkshopbcn.com

Secil Argamassas

Apartado 2, 2406-909 Maceira - Leiria PORTUGAL

Tel: +351 244 770 220 Fax.: +351 244 777 997

comercial@secilargamassas.pt www.secilargamassas.pt





ECOLOGICAL PRODUCT

SecilTEK SP 01
SILICATE PAINT

SecilTEK SP 01

SECILTEK SP 01 IS A WATER BASED SILICATE PAINT WITH **EXCELLENT WATER VAPOUR PERMEABILITY.**

SOLUTION FOR

- Decorative finish on facades, applied to Hydraulic substrates, natural stone, sprayed stucco, plasterboard, brick, **SecilVit CORK** external thermal insulation system, **REABILITA CAL** and **Secil ecoCORK Lime** systems
- Facade decorative finish, interior walls and ceilings, applied to trowled hydraulic renders

ADVANTAGES

- High permeability to water vapour
- Ecological paint
- Self cleaning
- Water resistant
- Resistant to the development of micro-organisms as fungi and algae
- Low consumption

SeciLTEK SPI

Available in 12 colours

TECHNICAL DATA

Interior and exterior walls

Substrates

Hydraulic, natural stone, sprayed stucco, plasterboard, brick, SecilVit CORK external thermal insulation system, **REABILITA CAL** Packaging and Secil ecoCORK Lime systems

Type of work

New Construction and Refurbishment

Application

Manual by roller

SecilTEK SP 01 is the ideal finishing for the following systems:

SecilVit CORK



REABILITA CAL



Secil ecoCORK Lime



Colour

Available in 12 colors

Theoretical consumption 8-10 m² / l / coat

15l Bucket Pallets of 33 buckets (495 l)

Water vapour transmission rate [Sd] 0.01 m

Permeability to vapour Class 1: < 0.14 (According to ISO 7783-2)

COLOUR REFERENCES:





The colours reproduce as faithfully as possible the supplied finishes however, slight variations are admitted, it is recommended to carry out tests before final application.